

Product Datasheet model astrospec 2.0 9164 065**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth****Product
characteristics**

- * Innovative style
- * Flexible 2K side arms and inclination
- * Secure and pressure-free fit
- * Wraparound side arms ensure perfect fit
- * Ventilation with labyrinth seal helps improve climate around the eyes
- * Panoramic polycarbonate lens with integrated side protectors for optimum coverage of the eyes
- * Folds flat

Technical details**Frame**Material
Colour**Front piece**PC+TPU
blueMaterial
Colour**Side piece**POM
grey

Material	Temple
Colour	PC+TPU/TPE blue-light blue
Manufacturer's ID code	Marking
Applicable EN norm	W
Low-energy impact	166
Resistance to high speed particles at extremes of temperat.	F (45 m/s)
Conformity symbol	T
	CE
Lens	
Material	PC
Thickness	2,2 mm
Coating	uvex supravision sapphire
Colour	clear
Filter	Marking
Manufacturer's ID code	2C-1,2 (DIN EN 170)
Optical class	W
Low-energy impact	1
Resistance to high speed particles at extremes of temperat.	F (45 m/s)
Surface resistance to fine particles	T
Conformity symbol	K
	CE
Miscellaneous	
Weight	37 g
Packing	5 spectacles per box 160 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 170